

# UMDE 36W P Series

## Medical AC/DC Adaptor



▲ UMDEI3036-XXXXXXPA



▲ UMDEB3036-XXXXXXPA



■ Please contact our sales department for safety standard of each model.



### Product Highlights

- Stability
- Compact Size
- Energy Efficiency
- Suit Medical Equipment, Health Device
- Peak Load 1.2 Sec Function
- The Peak Load is twice rating current. (Max.)
- For Amplifier Products/Printers/Voice Assistants/Motors/Pump
- 2xMOPP/2xMOOP
- IEC/EN 60601-1-2

### Efficiency

- Energy Efficiency Level VI ( ErP / DoE )
- Meet COMMISSION REGULATION(EU) 2019/1782
- Meet DOE 10 CFR part 429 and 430

### Protection

- Short Circuit Protection
- Over Voltage Protection
- Over Current Protection
- Over Temperature Protection (Optional)

### Emissions

- FCC Part18 Class B
- CE CISPR 11 EN55011
- VCCI Class B
- BS EN55011

### Safety Standard

- 60601-1
- PSE 別表第八

### Immunity

- EN60601-1-2
- BS EN60601-1-2

# Electrical Spec

Input					
Description	Min.	Typ.	Max.	Units	Comment
Voltage	90	100~240	264	Vac	
Frequency	47	50/60	63	Hz	

Environmental					
Description	Min.	Typ.	Max.	Units	Comment
Operating Temperature	0	-	40	°C	Free Convection,Sea Level
Storage Temperature	-20	-	65	°C	Free Convection,Sea Level
Operating Humidity	5	-	95	%RH	No Condensing
Storage Humidity	5	-	95	%RH	No Condensing

# Typical model list

改为240/240

No.	DC Output Voltage	DC Output Current	Output Voltage Precision	Ripple	Noise	DC Output Peak Current	Time (sec)	Average Active Efficiency	No-Load Power Consumption	Option/Remark
1	12.0V	3.0A	±5%	240mV	300mV	5.1A	1.2sec	-	-	
2	15.0V	2.4A	±5%	240mV	300mV	4.1A	1.2sec	-	-	
3	19.0V	1.9A	±5%	240mV	300mV	3.2A	1.2sec	-	-	
4	24.0V	1.5A	±5%	240mV	480mV	2.5A	1.2sec	-	-	

■ Measurement Condition

1. Measurements shall be made with an oscilloscope with 20MHz bandwidth.
2. Outputs shall be bypassed at the connector with a 0.1uF ceramic disk capacitor and a 10uF electrolytic capacitor to simulate system loading.

# Mechanical Spec

UMDEI3036 Series	UMDEB3036 Series

■ Please contact our sales department for details of each model ■