

# UWB 24W Series


## USB AC/DC Adaptor Foldable AC Plug / USB-A



▲ UWB324-USB4



■ Please contact our sales department for safety standard of each model.



### Product Highlights

- Stability
- Ultra Small Size
- Light Weight
- Energy Efficiency
- Suit MP3 Player, Mobile Phone, Portable GPS Device, PDA

### Protection

- Short Circuit Protection
- Over Voltage Protection
- Over Current Protection

### Safety Standard

- 60950-1
- 62368-1
- CNS14336
- PSE 別表第八

### Efficiency

- Energy Efficiency Level V

### Emissions

- CE CISPR 32 EN55032
- VCCI Class B
- CNS13438

### Immunity

- EN 55035

# Electrical Spec

Input					
Description	Min.	Typ.	Max.	Units	Comment
Voltage	90	100~240	264	Vac	
Frequency	47	50/60	63	Hz	

Environmental					
Description	Min.	Typ.	Max.	Units	Comment
Operating Temperature	0	-	40	°C	Free Convection,Sea Level
Storage Temperature	-20	-	65	°C	Free Convection,Sea Level
Operating Humidity	5	-	95	%RH	No Condensing
Storage Humidity	5	-	95	%RH	No Condensing


# Typical model list

Output Condition	DC Output Voltage	DC Output Current	Output Voltage Precision	Ripple	Noise	Option/Remark
USB-A	5.0V	4.2A	±5%	200mV	300mV	
	-	-	-	-	-	

■ Measurement Condition

1. Measurements shall be made with an oscilloscope with 20MHz bandwidth.
2. Outputs shall be bypassed at the connector with a 0.1uF ceramic disk capacitor and a 10uF electrolytic capacitor to simulate system loading.

# Mechanical Spec



■ Please contact our sales department for details of each model ■